




DIESEL FORKLIFT CATALOG



STARLIFT FORKLIFTS



QUALIFICATION CERTIFICATE



Our company adheres to the business philosophy of providing high-quality large-scale mechanical equipment for global users. We have rich experience in the design and manufacturing of engineering machinery, strong technical strength, advanced production equipment, and complete testing equipment. We are a modern enterprise that integrates production and sales. The company always adheres to the business philosophy of "seeking development through technology and creating a brand through quality"



Product Introduction

Simple and elegant appearance;

The new steering wheel adjustment mechanism improves operational comfort and adjustment reliability;

The high top large diameter intake system design can keep the engine away from dust, effectively unleash engine performance, and improve service life;

The wide field of view gantry design allows the driver's field of view to be wider;

Reliable LCD digital dedicated instrument panel, friendly human-machine interface, convenient for drivers to accurately control vehicle status;

Optional cast steering axle, low maintenance cost in the later stage.

类型 Type	四轮座驾式柴油叉车 Four wheel drive diesel forklift					
型号 Model	Qpc-12	Qpc-15	Qpc-20	Qpc-26	Qpc-30	Qpc-35
发动机 Engine	常州单缸	常州单缸	四缸 490	四缸 490	四缸 490	四缸 490
整机重量 kg Overall weight	1500	2400	2800	3100	3600	4000
整机尺寸 mm Overall dimensions	2300*1250*2200	2350*1250*2200	2900*1300*2200	2900*1300*2200	2900*1300*2200	2950*1350*2200
轴距 mm Wheelbase	1370	1370	1730	1730	1730	1730
最小离地间隙 mm Ground clearance	170	170	200	200	170	170
最大爬坡度 Gradient	10°	10°	10°	10°	10°	10°
速度 km/h Speed	20-28	20-28	20-28	20-28	20-28	20-28
轮胎型号 Tire model	600-14/500-8	600-14/500-8	650-16/600-9	1000/70-16/600-9	28*9-15/650-10	28*9-15/650-10
最小转弯半径 mm Turning radius	2800	2400	2400	2400	2400	2400
额定起重量 kg Rated lifting capacity	1000	1500	2000	2600	3000	3500
货叉长度 mm Fork length	1070	1070	1070	1070	1070	1200
货叉外侧最大调节度 Fork adjustment degree	1100	1100	1100	1100	1100	1100
载荷中心距 mm Load center distance	450	450	500	500	500	500
门架前倾角 Front tilt angle of the gantry	10	10	10	10	10	10
门架后倾角 Gantry tilt angle	8	8	8	8	8	8
最大起升高度 mm Maximum lifting height	1650	3000	3000	3000	3000	3000

ECONOMIC FUNDS

INTERNAL COMBUSTION FORKLIFT SERIES



BEIQIANG HOMOY MODEL



Product Introduction

Simple and elegant appearance, with strict environmental design;

The new steering wheel adjustment mechanism improves operational comfort and adjustment reliability;

The wide field of view gantry design allows the driver's field of view to be wider;

The high top large diameter intake system design can keep the engine away from dust, effectively unleash engine performance, and improve service life;

Reliable LCD digital dedicated instrument panel, friendly human-machine interface, convenient for drivers to accurately control vehicle status;

Optional cast steering axle, low maintenance cost in the later stage.

K-SERIES

INTERNAL COMBUSTION FORKLIFT

类型 Type	K 系列四轮座驾式柴油叉车 K series four wheel drive diesel forklift					
型号 Model	opc-15	opc-20	opc-25	opc-30	opc-35	opc-40
发动机 engine	全柴/新柴 490	全柴/新柴 490	全柴/新柴 490	全柴/新柴 490	全柴/新柴 490	全柴/新柴 495
整机重量 kg Overall weight	2900	3320	3680	4250	4500	4800
整机尺寸 mm Overall dimensions	2260*1090*2100	2500*1170*2100	2576*1170*2100	2685*1225*2200	2700*1225*2200	2930*1290*2200
轴距 mm Wheelbase	1400	1600	1600	1700	1700	1900
最小离地间隙 mm Ground clearance	110	110	110	135	135	140
最大爬坡度 Gradient	20°	20°	20°	20°	20°	20°
速度 km/h Speed	14-15	17-19	17-19	18-19	18-19	19-19
轮胎型号 Tire model	6.5-10/5.0-8-10	7.0-12/6.0-9-10	7.0-12/6.0-9-10	28*9-15-14/6.5-10	28*9-15-14/6.5-10	28*9-15-14/6.5-10
最小转弯半径 mm Turning radius	1950	2170	2240	2400	2400	2710
额定起重量 kg Rated lifting capacity	1500	2000	2500	3000	3500	4000
货叉长度 mm Fork length	1070	1070	1070	1070	1070	1220
货叉外侧最大调节度 Fork adjustment degree	1100	1100	1100	1100	1100	1100
载荷中心距 mm Load center distance	500	500	500	500	500	600
门架前倾角 Front tilt angle of the gantry	6	6	6	6	6	6
门架后倾角 Gantry tilt angle	12	12	12	12	12	12
最大起升高度 mm Maximum lifting height	3000	3000	3000	3000	3000	3000



BEIQIANG K-SERIES



Product Introduction

Multiple domestic and imported engines meet European and American standards

Hydraulic power steering;

Adopting multiple new technologies and structures, with a streamlined design and beautiful appearance;

Small and agile in appearance; Absorbed various advantages of modern forklift technology;

The overall performance and manufacturing technology have reached the first-class level in China;

Comfortable operation and ergonomic driving environment

FOREIGN TRADE SERIES

LPG FORKLIFT



类型 type	LPG 四轮座驾式叉车 LPG four-wheel drive forklift					
型号 model	LPG-15	LPG-20	LPG-25	LPG-30	LPG-35	LPG-40
发动机 engine	安徽广庆/尼森	安徽广庆/尼森	安徽广庆/尼森	安徽广庆/尼森	安徽广庆/尼森	安徽广庆/尼森
整机重量 kg Overall weight	2900	3320	3680	4250	4500	4900
整机尺寸 mm Overall dimensions	2260*1090*2100	2500*1170*2100	2576*1170*2100	2485*1225*2200	2700*1225*2200	2930*1290*2200
轴距 mm Wheelbase	1400	1600	1600	1700	1700	1900
最小离地间隙 mm Ground clearance	110	110	110	135	135	140
最大爬坡度 Gradient	20°	20°	20°	20°	20°	20°
速度 km/h Speed	14-15	17-19	17-19	18-19	18-19	19-19
轮胎型号 Tire model	6.5-10/5.0-8-10	7.0-12/6.0-9-10	7.0-12/6.0-9-10	28*9-15-14/6.5-10	28*9-15-14/6.5-10	28*9-15-14/6.5-10
最小转弯半径 mm Turning radius	1950	2170	2240	2400	2400	2710
额定起重量 kg Rated lifting capacity	1500	2000	2500	3000	3500	4000
货叉长度 mm Fork length	1070	1070	1070	1070	1070	1220
货叉外侧最大调节度 Fork adjustment degree	1100	1100	1100	1100	1100	1100
载荷中心距 mm Load center distance	500	500	500	500	500	600
门架前倾角 Front tilt angle of the gantry	6	6	6	6	6	6
门架后倾角 Gantry tilt angle	12	12	12	12	12	12
最大起升高度 mm Maximum lifting height	3000	3000	3000	3000	3000	3000



Product Introduction

Adopting a fully hydraulic steering device, with a small turning radius, lightweight and flexible steering, safe and reliable;

The design of the high-level intake system can keep the engine away from dust, effectively unleash engine performance, and improve service life;

The design of low position instrument panel and wide field of view door frame makes the driver's field of view more open;

Recent manufacturing processes and high-quality components ensure high reliability of the entire vehicle;

Forklifts with different hydraulic and mechanical transmission systems can be selected as required;

类型 Type	K 系列四轮座驾式柴油叉车 K series four wheel drive diesel forklift					
型号 model	K-50	Qcd-50	Qcd-60	Qcd-70	Qcd-80	Qcd-100
发动机 engine	金柴/新柴 498	金柴/新柴 498 增压	金柴 4J1-115G32	金柴 4J1-115G32	金柴 4J1-115G32	金柴 4J1-115G32
整机重量 kg Overall weight	5500	6700	8900	9600	10800	12400
整机尺寸 mm Overall dimensions	3050*1290*2200	3120*1480*2240	3500*1970*2500	3680*1970*2500	3830*2100*2550	4277*2250*2570
轴距 mm Wheelbase	1900	2000	2250	2250	2800	2800
最小离地间隙 mm Ground clearance	150	175	230	230	250	250
最大爬坡度 Gradient	20°	20°	20°	20°	20°	20°
速度 km/h Speed	18-19	18-19	23-29	23-29	20-26	20-26
轮胎型号 Tire model	300-15-20/7.0-12	300-15-20/7.0-12	8.25-15-14PR	8.25-15-14PR	8.25-15-14PR	9.00-20NR5
最小转弯半径 mm Turning radius	2820	2900	4120	4180	3755	4150
额定起重量 kg Rated lifting capacity	5000	5000	6000	7000	8000	10000
货叉长度 mm Fork length	1070	1070	1070	1070	1520	1520
自由起升高度 mm Free lifting height	160	160	210	210	200	200
载荷中心距 mm Load center distance	500	500	600	600	600	600
门架前倾角 Front tilt angle of the gantry	6°	6°	6°	6°	10°	10°
门架后倾角 Gantry tilt angle	12°	12°	12°	12°	12°	12°
最大起升高度 mm Maximum lifting height	3000	3000	3000	3000	3000	3000

K-SERIES

INTERNAL COMBUSTION FORKLIFT



Product Introduction

Designed according to the principles of ergonomics, the operation is more comfortable;

Optimize design, effectively extend the service life of the engine, and improve the reliability of the entire machine;

Adopting drum brakes and fully hydraulic power braking, making operation more lightweight, comfortable, and reliable;

The design of a wide field of view forming groove gate frame allows the driver's field of view to be wider;

Beautiful and generous in appearance, with clear contours and lines;

Adopting a new type of steering wheel adjustment mechanism to improve operational comfort and adjustment reliability;

Advanced manufacturing technology and high-quality components ensure high reliability of the entire vehicle.

类型 type	铰接款前转向四驱越野叉车 Articulated front steering four-wheel drive off-road forklift				
型号 model	OPCD-15	OPCD-30	OPCD-35	OPCD-40	OPCD-50
发动机 engine	云内 490	云内 490	云内 490 增压	云内 4100 增压	云内 4102 增压
轮胎 Tire model	半实心 10.00-16	20.5/70-16 钢丝	20.5/70-16 钢丝	16/70-20 钢丝	16/70-24 半实心
变速箱 Transmission	265	265	265	280	280
门架宽度 mm Gate frame width	148mm	160mm	160	180	180
爬坡角度° Climbing angle	<35°	<35°	<35°	<35°	<35°
车架铰接 mm Frame hinge	200mm /150mm	300mm /250mm	300mm/250mm	400mm/300mm	500mm/300mm
整机重量 kg Overall weight	2680	4390	4410	5200	5700
前倾角度° Forward tilt angle	12°	12°	12°	12°	12°
外观尺寸 mm Appearance dimensions	3160*1300*2300	4150*1800*2450	3900*1800*2450	4300*1980*2600	4400*2685*2650
最大载量 kg Maximum load capacity	1500	3000	3500	4000	5000
连接桥 Connecting bridge	130 加重铸钢桥	小轮边加重铸钢桥	小轮边加重铸钢桥	中轮边加重铸钢桥	大轮边加重铸钢桥
转弯半径 mm Turning radius	4500	4500	4500	4800	4800
举升高度 mm Lifting Height	3000	3000	3000	3500	3000
货叉长度 mm Fork length	1220	1220	1220	1220	1220
最小离地间隙 mm Minimum ground clearance	250	240	240	300	330
门架静止高度 mm Gate frame static height	2220	2200	2200	2350	2400



北强机械
BEIQIANG OFF-ROAD FORKLIFT



Product Introduction

The wide field of view gantry design allows the driver's field of view to be wider;

The high intake system design can keep the engine away from dust, effectively unleash engine performance, and improve service life;

Reliable LCD digital dedicated instrument panel, friendly human-machine interface, convenient for drivers to accurately control vehicle status;

Low noise, low vibration, energy-saving and environmentally friendly;

Advanced manufacturing technology and high-quality components ensure high reliability of the entire vehicle;

The design is beautiful and elegant, with clear contours and lines.



FOUR WHEEL DRIVE OFF-ROAD FORKLIFT
ARTICULATED REAR STEERING

四驱越野叉车
ARTICULATED REAR STEERING
FOUR WHEEL DRIVE OFF-ROAD FORKLIFT



类型 Type	铰接款后转向四驱越野叉车 Articulated rear steering four-wheel drive off-road forklift				
型号 model	OPCD-30	OPCD-35	OPCD-40	OPCD-50	OPCD-60
发动机 engine	云内 490	云内 490	云内 4102 增压	云内 4102 增压	云内 4102 增压
轮胎 Tire model	20.5/70-16 加宽加后	20.5/70-16 半实心	16/70-20 钢丝	16/70-24 半实心	12R22.5
变速箱 Transmission	265	265	280	280	280
门架宽度 mm Gate frame width	160	160	180	180	180
爬坡角度° Climbing angle	<35°	<35°	<35°	<35°	<35°
车架铰接 mm Frame hinge	200mm /250mm	200mm /250mm	200mm/250mm	250mm/300mm	250mm/300mm
整机重量 kg Overall weight	4200	4400	5200	5700	6300
前倾角度° Forward tilt angle	12°	12°	12°	12°	12°
外观尺寸 mm Appearance dimensions	3650*1800*2450	3700*1800*2450	3800*1980*2500	3900*2080*2650	4000*2400*2600
最大载量 kg Maximum load capacity	3000	3500	4000	5000	6000
连接桥 Connecting bridge	小轮边加重铸钢桥	小轮边加重铸钢桥	中轮边加重铸钢桥	大轮边加重铸钢桥	大轮边加重铸钢桥
转弯半径 mm Turning radius	3600	3600	3600	3900	4100
举升高度 mm Lifting Height	3000	3000	3000	3000	3000
货叉长度 mm Fork length	1220	1220	1220	1220	1220
最小离地间隙 mm Minimum ground clearance	250	250	300	330	330
门架静止高度 mm Gate frame static height	2240	2240	2300	2330	2330

FOUR WHEEL DRIVE OFF-ROAD FORKLIFT

MID HINGED VERSION



类型 Type	后铰接款后转向四驱越野叉车 Rear articulated rear steering four-wheel drive off-road forklift		
型号	Model	GPCY35	GPCY50
发动机功率 kw	Engine power kw	36.8	36.8-81
整机重量 kg	Total weight kg	5200-5500	7000
整机尺寸 mm	Overall size mm	3350*1850*2200	4100*2000*2300
轴距 mm	Wheelbase mm	1740	1900
最小离地间隙 mm	Minimum ground clearance mm	260	360
最大爬坡度(满载)	Maximum Climbing Slope (Full Load)	25	25
速度(空载高度) km/h	Speed (unloaded height) km/h	28-35	28-35
前轮/后轮	Front wheel/rear wheel	20.5/70-16	16/70-24
最小转弯半径 mm	Minimum turning radius mm	3000	4000
额定起重量 kg	Rated lifting capacity kg	3500	5000
货叉长度 mm	Fork length mm	1070	1070
货叉最大调节度 mm	Maximum adjustment degree of fork mm	1100	1100
载荷中心距 mm	Load center distance mm	500	500
门架前倾角°	Front inclination angle of the gantry	6°	6°
门架后倾角°	Gantry tilt angle °	12°	12°
最大起升高度 mm	Maximum lifting height mm	3000	3000



类型 type	中铰接款后转向四驱越野叉车 Mid articulated rear steering four-wheel drive off-road forklift		
型号	Model	GPCY35	GPCY50
发动机功率 kw	Engine power kw	36-42	36.8-81
整机重量 kg	Total weight kg	5200-5500	7000
整机尺寸 mm	Overall size mm	3600*1850*2200	4100*2000*2300
轴距 mm	Wheelbase mm	1800	1900
最小离地间隙 mm	Minimum ground clearance mm	260	360
最大爬坡度(满载)	Maximum Climbing Slope (Full Load)	25	25
速度(空载高度) km/h	Speed (unloaded height) km/h	28-35	28-35
前轮/后轮	Front wheel/rear wheel	20.5/70-16	16/70-24
最小转弯半径 mm	Minimum turning radius mm	3000-3500	4000
额定起重量 kg	Rated lifting capacity kg	3500	5000
货叉长度 mm	Fork length mm	1070	1070
货叉最大调节度 mm	Maximum adjustment degree of fork mm	1100	1100
载荷中心距 mm	Load center distance mm	500	500
门架前倾角°	Front inclination angle of the gantry °	6°	6°
门架后倾角°	Gantry tilt angle °	12°	12°
最大起升高度 mm	Maximum lifting height mm	3000	3000

FOUR WHEEL DRIVE OFF-ROAD FORKLIFT

REAR HINGED VERSION



ONE PIECE CLASSIC STYLE
FOUR WHEEL DRIVE OFF-ROAD FORKLIFT



类型 Type	豪华款一体式四驱越野叉车 Luxury all-in-one four-wheel drive off-road forklift		
型号 Model		GPCY35	GPCY40
发动机 engine		全柴 495	全柴 495 增压
整机重量 kg Total weight kg		5200-5500	5800
整机尺寸 mm Overall size mm		2980*1500*2130	2980*1500*2130
轴距 mm Wheelbase mm		1750	1750
最小离地间隙 mm Minimum ground clearance mm		220	260
最大爬坡度(满载) Maximum Climbing Slope (Full Load)		25	25
速度(空载高度) km/h Speed (unloaded height) km/h		28-35	28-35
前轮/后轮 Front wheel/rear wheel		10-16.5 半实心	10-16.5 半实心
最小转弯半径 mm Minimum turning radius mm		2800	2800
额定起重量 kg Rated lifting capacity kg		3500	4000
货叉长度 mm Fork length mm		1070	1070
货叉最大调节度 mm Maximum adjustment degree of fork mm		1100	1100
载荷中心距 mm Load center distance mm		500	500
门架前倾角° Front inclination angle of the gantry		6°	6°
门架后倾角° Gantry tilt angle °		12°	12°
最大起升高度 mm Maximum lifting height mm		3000	3000



类型 type	经典款一体式四驱越野叉车 Classic all-in-one four-wheel drive off-road forklift					
型号 model	Qpoy-30 后轮转向	Qpoy-30 四轮转向	Qpoy-35 后轮转向	Qpoy-40 后轮转向	Qpoy-40 四轮转向	Qpoy-50 四轮转向
发动机 engine	锡柴 490	锡柴 490 增压	锡柴 490 增压	云内 4102	锡柴 4102	朝柴 6102
整机重量 kg Overall weight	4500-5200	4500-5200	4500-5200	5200	6200	7800
整机尺寸 mm Overall dimensions	3350*1700*2300	3350*1700*2300	3350*1700*2300	3500*1850*2500	3500*1850*2500	3600*1880*2600
轴距 mm Wheelbase	1600	1600	1600	1740	1740	2500
最小离地间隙 mm Ground clearance	280	280	280	320	320	350
最大爬坡度 Gradient	30°	30°	30°	30°	30°	30°
速度 km/h Speed	20-35	25-35	20-35	20-35	20-35	25-35
轮胎型号 Tire model	12-16.5/10-16.5	12-16.5/10-16.5	12-16.5/10-16.5	12-16.5/10-16.5	12-16.5/10-16.5	20.5/70-16
最小转弯半径 mm Turning radius	3500	3200	3500	3700	3200	3250
额定起重量 kg Rated lifting capacity	3000	3000	3500	4000	4000	5000
货叉长度 mm Fork length	1070	1070	1070	1220	1220	1220
连接桥 Connecting bridge	轮边加重铸钢桥	轮边加重铸钢桥	轮边加重铸钢桥	轮边加重铸钢桥	轮边加重铸钢桥	轮边加重铸钢桥
载荷中心距 mm Load center distance	500	500	500	600	600	600
门架前倾角 Front tilt angle of the gantry	12	12	12	12	12	12
门架后倾角 Gantry tilt angle	8	8	8	8	8	8
最大起升高度 mm Maximum lifting height	3000	3000	3000	3000	3000	3000

INTEGRATED LUXURY EDITION
FOUR WHEEL DRIVE OFF-ROAD FORKLIFT



TWO WHEEL DRIVE REAR STEERING
NEW INTEGRATED OFF-ROAD FORKLIFT



类型 type	新款一体式四驱后转向越野叉车 New integrated four-wheel drive rear steering off-road forklift			
型号 model	GPC25Y4X	GPC30Y4X	GPC35Y4X	GPC40Y4X
发动机 engine	新柴 495	全柴 4C2-504C43	全柴 4C2-504C43	全柴 4C2-504C43
整机重量 kg Overall weight	4650	4800	5850	6100
整机尺寸 mm Overall dimensions	2940*1550*2300	2940*1550*2300	3260*1630*2300	3350*1700*2300
轴距 mm Wheelbase	1850	1850	1990	2100
最小离地间隙 mm Ground clearance	220	220	220	220
最大爬坡度 Gradient	20-30°	20-30°	20-30°	20-30°
速度 km/h Speed	22	22	22	22
轮胎型号 Tire model	12-16.5-14/27x10.5-15	12-16.5-14/27x10.5-15	14-17.5NHS/10/75-15.31MP	14-17.5NHS/10/75-15.31MP
最小转弯半径 mm Turning radius	2910	2910	3450	3450
额定起重量 kg Rated lifting capacity	2500	3000	3500	4000
货叉长度 mm Fork length	1070	1070	1070	1070
起升速度 mm/s Lifting speed	450	440	420	420
载荷中心距 mm Load center distance	500	500	500	500
门架前倾角 Front tilt angle of the gantry	8	8	8	8
门架后倾角 Gantry tilt angle	12	12	12	12
最大起升高度 mm Maximum lifting height	3000	3000	3000	3000



FOUR WHEEL DRIVE REAR STEERING

NEW INTEGRATED OFF-ROAD FORKLIFT



类型 Type	新款一体式两驱后转向越野叉车 New integrated two wheel drive rear steering off-road forklift			
型号 Model	CPC25Y	CPC30Y	CPC35Y	CPC40Y
发动机 Engine	新柴 495	全柴 4C2-504C43	全柴 4C2-504C43	全柴 4C2-504C43
整机重量 kg Overall weight	4650	4800	4950	5850
整机尺寸 mm Overall dimensions	2980*1550*2185	2950*1550*2200	2980*1550*2200	3260*1630*2300
轴距 mm Wheelbase	1850	1850	1850	1990
最小离地间隙 mm Ground clearance	220	220	220	200
最大爬坡度 Gradient	20°	20°	20°	20°
速度 km/h Speed	22	22	22	22
轮胎型号 Tire model	12-16.5-14/27x10.5-15	12-16.5-14/27x10.5-15	14-17.5-16/10-16.5-12	14-17.5NHS/10/75-15.3IMP
最小转弯半径 mm Turning radius	2910	2910	2930	3450
额定起重量 kg Rated lifting capacity	2500	3000	3500	4000
货叉长度 mm Fork length	1070	1070	1070	1070
起升速度 mm/s Lifting speed	450	440	420	420
载荷中心距 mm Load center distance	500	500	500	500
门架前倾角 Front tilt angle of the gantry	8	8	8	8
门架后倾角 Gantry tilt angle	12	12	12	12
最大起升高度 mm Maximum lifting height	3000	3000	3000	3000




Multiple accessories can be freely matched



FLAT HUG CLIP



DUSTPAN



TIPPING BUCKET



TELESCOPIC ARM




PUSHER



PAPER ROLL CLIP



SOFT HUG CLIP



ROTATING FORK



TWO-TOOTH UPPER GRAB



INSERT BUCKET



LATERAL TRANSFER DEVICE



SINGLE HOOK ARM





— GREAT PRICE, GREAT QUALITY! —

